

The Apollo Mini Series of Industrial Radio Remote Controls are best suited for simple applications where minimal directional control is required (e.g. tail lifts, wreckers, gates/doors, etc.). This compact system offers a small, lightweight package with two, three, or four functions and an IP65 rated enclosure and 30 meter range.

Available Models

MINI20	1 step, (2) buttons
MINI30	1 step, (3) buttons
MINI40	1 step, (4) buttons

Transmitter Specifications

Operating Range	30 M (LOS)
Frequency	FM 418 MHz
Response Time	100 ms
Output Power	< 10 mW
Operating Temperature	0°- +70° C (32°-158° F)
Antenna	Internal
Power Supply	1.5 V (2 AA Alkaline Batteries)
Ingress Protection	IP65
Material	Industrial ABS PC
Address Codes	256
Weight	95 g (Excluding Batteries)
Dimensions	124 × 48 × 25mm

Receiver Specifications

Frequency	FM 418MHz
RF Sensitivity	-110 dBm
Antenna	Internal
Operating Temperature	-10°- +75° C (14°-167° F)
Antenna	Internal
Power Supply	9-30 VDC
Ingress Protection	IP65
Address Codes	256
Weight	270 g (Excluding Cable)
Power Consumption	<12W



Applications

- Reel Control
- Hoist Control
- Gate/Door Control

Options

- 2, 3, or 4 Functions
- AC or DC Receiver Power



005WWCA0358
005WWCA0359

